




FEATURES

- 1/4" CCD high quality image sensor
- Ultra compact camera
- Automatic Electronic Iris
- Vandal resistant & waterproof housing
- Extra-wide field of view
- Wide operating temperature range (-30°C to +50°C)
- Input voltage: DC 12V from monitor



Camera input connector pin description.




Pin No.	Description
1	Video Output (WHITE)
2	N / C
3	N / C
4	Power DC 12V (YELLOW)
5	Ground (BLACK)


CAMERA INSTALLATION

A. Attach the supplied mounting bracket to the vehicle.

Adjust the angle of the camera and fasten the screws firmly.



B. Run the cable from the monitor to the camera



SPECIFICATIONS

- Image Interline transfer type CCD
- Picture elements NTSC : 270,000 pixels PAL : 320,000 pixels
- Image size 1/4 Inch
- Lens Focal length 2.5mm , Maximum aperture F=2.5
- Viewing angle 150° (D) , 120° (H) , 90° (V)
- Synchronization Internal
- Horizontal resolution 330TV lines
- Required illumination 1.0 Lux Minimum
- Signal to noise ratio Minimum 48dB (at AGC off)
- Power supply DC 12V
- Power consumption 1.2W (Max)
- Operating temp. -30°C to +50°C (-22°F to +122°F)
- Weight 0.05Kg
- Dimensions 33(W) X 25(H) X 36(D) mm(1.3(W) X 1.0(H) X 1.4(D) Inch)

※ Design And Specifications Are Subject To Change Without Notice.

BRIGADE®

Brigade Electronics Plc. Brigade House, The Mills, Station Road, South Darenth, Kent DA4 9BD
 Sales Tel: 0870 774 1500 Admin Tel: 0870 774 1501 Fax: 0870 774 1502
 www.brigade-electronics.com support@brigade-electronics.com

