




FEATURES

- You can use the camera by a DC 12V / 200mA
- The camera utilizes a CCD image sensor having a high quality picture.
- The camera automatically adjusts the picture quality with changing in light.
- Water-resistant housing.
- Operates over a wide temperature range.




Camera input connector pin description.




Pin No.	Description
1	Video Output - WHITE
2	Tilt Control Power DC 9V - BLUE
3	Audio Output - RED
4	Power DC 12V - YELLOW
5	Ground - BLACK

CAMERA INSTALLATION

A. Attach the supplied mounting bracket to the vehicle. Adjust the angle of the camera and fasten the screws firmly.



B. Run the cable from the monitor to the camera



SPECIFICATIONS

- Image Interline transfer type CCD
- Picture elements NTSC : 270,000 pixels PAL : 320,000 pixels
- Image size 1/3 Inch
- Lens Focal length 2.9mm , Maximum aperture F=2.0
- Synchronization Internal
- Horizontal resolution 330TV lines at Center
- Required illumination 1.5 Lux Minimum
- Signal to noise ratio Minimum 46dB (at AGC off)
- Power supply DC 12V
- Power consumption 2.4W
- Operating temp. -30°C to +50°C (-22°F to +122°F)
- Weight 0.5Kg
- Dimensions 91(W) X 53(H) X 78(D) mm
3.6(W) X 2.1(H) X 3.1(D) Inch

※ Design And Specifications Are Subject To Change Without Notice.