

## SELECT RANGE CAMERA



**VBV-710C - Heated shutter camera 2808**

For connection to VBV-770DM-S and VBV-750DM-S 5-pin Select monitors  
Requires 5-pin 10m (VBV-L510) or 20m (VBV-L520) camera cable

**VBV-710C(AC) - Heated shutter camera 3703**

Includes 5-pin to 4-pin adapter (AC-035) for connection to other Select monitors

▪ **Viewing angle (HxVxD)**  
85 x 62 x 110°

▪ **IP69K**

▪ **Size (WxHxD)**  
122 x 82 x 83mm

▪ **2 year warranty**



### Features

- 12 Infrared LEDs for ultra-low light performance
- 10m illumination distance
- Shutter
- Heater
- Audio
- Day / Night sensor
- Mirror / Normal view
- 1/3" Sony CCD
- TV System: PAL
- TV Lines: 420

### Power

- Power consumption: 6 Watts
- Current: 0.43 Amps

### Durability & Standards

- Mechanical vibration: 25G
- Operating temperature: -20 to +70°C
- CE Marked
- EMC approved: e

Brigade Electronics Plc  
Brigade House, The Mills, Station Road, South Darenth, Kent DA4 9BD  
Telephone +44(0) 1322 420300 Facsimile +44(0) 1322 420343  
Email sales@brigade-electronics.com www.brigade-electronics.com

