

## SELECT RANGE CAMERA



**VBV-711C - Heated shutter camera 2841**

For connection to VBV-770DM-S and VBV-750DM-S 5-pin Select monitors  
Requires 5-pin 33' (VBV-L510) or 66' (VBV-L520) camera cable

**VBV-711C(AC) - Heated shutter camera 3708**

Includes 5-pin to 4-pin adapter (AC-035) for connection to other Select monitors

▪ **Viewing angle (HxVxD)**  
85 x 62 x 110°

▪ **IP69K**

▪ **Size (WxHxD)**  
4.8 x 3.2 x 3.2 inches

▪ **2 year warranty**



### Features

- 12 Infrared LEDs for ultra-low light performance
- 33' illumination distance
- Shutter
- Heater
- Audio
- Day / Night sensor
- Mirror / Normal view
- 1/3" Sony CCD
- TV System: NTSC
- TV Lines: 420

### Power

- Power consumption: 6 Watts
- Current: 0.43 Amps

### Durability & Standards

- Mechanical vibration: 25G
- Operating temperature: -4 to +158°F
- CE Marked
- EMC approved: e

Brigade Electronics Inc  
226 S.Meridian St, Portland, IN 47371 USA  
Tel: +1 (260) 766-4343 email: infousa@brigade-electronics.com  
www.brigade-inc.com

