



**NOTES/SPECIFICATION**

1. POWER INPUT: DC12-32V.
2. POWER CONSUMPTION: MAX. 10 WATTS.
3. VIDEO SIGNAL: NTSC, PAL STANDARD SYSTEM.
4. SYNC. SYSTEM: INTERNAL.
5. LCD PANEL SIZE: 5.6 INCH DIAGONAL.
6. ANGLE OF VIEW: TOP: 11°, BOTTOM: 30°, LEFT: 45°, RIGHT: 45°.
7. SCREEN SIZE: 113.31W x 234.1H mm
8. SCREEN RESOLUTION: 960W x 234.1H mm
9. DIMMER: AUTOMATIC
10. COLOUR CONFIGURATION: R, G, B STRIPE
11. OSD CONTROL: VOLUME, BRIGHTNES, SCALE ON/OFF, IMAGE SELECT, MIRROR/NORMAL, AUTO SCAN ON/OFF, 2 AUTO TRIGGERING, COLOUR, CONTRAST, TINT, INTSC ON, YI, VIDEO SIGNAL INTSC/PAL
12. POWER CONNECTOR: 4 PIN WIRE
13. CAMERA CONNECTION: 2 MINI-DIN
14. SPEAKER: IMPEDANCE 8ohms, 1.2 WATT MAX.
15. FINISH: LIGHT BLACK (ABS)
16. OPERATING TEMPERATURE: -10°C ~ 50°C
17. STORAGE TEMPERATURE: -25°C ~ 80°C
18. VIBRATION: 4G
19. DIMENSION: 172(W) x 115(H) x 28(D)mm
20. WEIGHT: 1.1Kg
21. REMOTE CONTROL: NO - UNDER DEVELOPMENT
22. CAMERAS: BE-255C/BE-856C/BE-810C/810C/BE-201C/210C/BE-901C/101C

**POWER/TRIGGER WIRE FUNCTIONS**

REF #	WIRE COLOR	DESCRIPTION
1	RED	12/24Vdc (POSITION)
2	BLACK	0Vdc (NEGATIVE)
3	GREEN	TRIGGER 1 (CA1)
4	WHITE	TRIGGER 2 (CA2)

**PROPRIETARY NOTICE**  
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC

Item#	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by DKERAL	Checked by DKERAL	Approved by - date DKERAL - 21/10/15	File name BE-856BM
BRIGADE ELECTRONICS		BE-100335-01-05	BE-856BM
Date 29/10/15			Article No./Reference BE-856BM
Edition A			Scale 1:1
Sheet 1/1			Scale 1:1