

MONITOR - BV-155 M

Features:

Two camera inputs
 Automatic "screen on" when reversed gear engaged
 Camera one and camera two selector button
 Mirror and normal image selection
 10G Mechanical Vibration
 Brightness and Contrast control
 Day/Night Switch



Specification:

Picture Tube:	5.5" inch B/W CRT
Deflection angle:	70°C
Power consumption:	100 mA maximum
Input voltage:	11-32 vdc
Output voltage:	10 vdc
TV System:	CCIR/EIA
Video Input/Output:	Composite Video Single 1Vp-p 75 ohm
Resolution:	600 TV lines
Operating temperature:	0°C ~ to +60°C
Storage temperature range:	-25°C ~ +70°C
Weight:	1.46 kg
Dimensions (W x H x D)mm:	154 x 143 x 190

CAMERA - BV-155 C

Features:

Waterproof without extra housing needed
 Night vision available
 15G Mechanical Vibration



Specification:

Power source:	12vdc
TV System:	CCIR/EIA
Image device:	1/3" CCD
Effective pixels:	CCIR (500x580) pixels, EIA (510x492) pixels
Resolution:	420 TV lines
Minimum illumination:	0 lux
Current consumption:	360 mA
Video Output:	1.0 Vp-p, 75 Ohm
Operating Temperature:	-10°C to +45°C
Storage Temperature:	-30°C to +60°C
Lens Angle:	92°
Weight:	0.2 kg
Dimensions (W x H x D)mm:	70 x 44 x 54

REVISIONS

REV	DESCRIPTION	DATE	APPROVED
A	RELEASED	21/06/04	B.KHEZR

PROPRIETARY NOTICE

THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.



BV-155 SYSTEM

SIZE	STOCK CODE:	DWG NO BE-SP-00015-00-04	REV A
SHEET		1 OF 1	