

VBV-750AM MONITOR

PICTURE TUBE5.0 inch, COLOUR TFT-LCD
DEFLECTION ANGLE..... 45° (LEFT/RIGHT), 10° (TOP), 30° (DOWN)
POWER SOURCE12-24 Vdc (WITH USE OF CONTROL BOX)
POWER CONSUMPTION..... ~ 8W/700mA MAXIMUM
OUTPUT VOLTAGE..... 9.6Vdc
TV SYSTEMPAL/NTSC
VIDEO INPUT/OUTPUTCOMPOSITE VIDEO SINGLE 1VP-P 75 OHM
RESOLUTION..... 960(H) x 234(V)
CONTRAST150:1
VIEWING ANGLE (U x D x R/L)15 x 35 x 50
OPERATING TEMPERATURE..... -10°C TO +60°C
STORAGE TEMPERATURE..... -25°C TO +70°C
WEIGHT0.43Kg
DIMENSIONS (W x H x T) mm165 x 126 x 31

VBV-700CM CONTROL BOX

POWER INPUT12-32 Vdc
POWER OUTPUT11-12 Vdc, 2A
POWER CONSUMPTION MAX..... 20 W
VIDEO OUTPUT..... 1V P-P 75 OHM
VOLTAGE OUTPUT..... 12 Vdc to camera
OPERATING TEMPERATURE..... -10° TO +60°C
STORAGE TEMPERATURE..... -25° TO +80°C
CASE MATERIALALNICO
WEIGHT..... ~0.5 Kg
DIMENSIONS (W x H x D) mm118 x 36 x 79