

BEST SELLER

SELECT RANGE MONITOR



VBV-750DM -	5" Digital LCD monitor	3280
VBV-750DM-S -	5" Digital LCD monitor Includes 1 5-pin input for connection to VBV-710C shutter camera	3982
VBV-750DM(R46) -	5" Digital LCD monitor R46 and 2003/97/EC approved for indirect vision (For use with specific cameras only - see Camera Monitor intro page for details)	3981

- **12-24Vdc**
- **3 camera inputs**
- **Size (WxHxD)**
148 x 110 x 31.5mm
- **2 year warranty**



Features

- 3 Auto-triggers
- Mirror / Normal switching from menu
- On-screen distance markers
- 'Button lock' anti-tamper feature
- Audio
- Sun shield
- Auto-dimmer
- Multi-lingual menus
- Auto-switching PAL / NTSC

Picture Quality

- LED backlighting (gives 20,000 hours life)
- Anti-glare screen
- Resolution: 640 x 3 x 480

- Contrast ratio: 500:1
- Brightness: 200cd/m²
- Viewing angles:
Side 70° x Top 50° x Bottom 70°

Power

- Power consumption: 5 Watts
- Current: 0.18 Amps

Durability & Standards

- Mechanical vibration: 10G
- Mechanical shock: 100G
- Operating temperature: -20 to +70°C
- CE marked
- EMC approved: e
- HALT tested

