

BEST SELLER**SELECT RANGE MONITOR****VBV-750DM -**
VBV-750DM-S -**5" Digital LCD monitor****5" Digital LCD monitor**

Includes 1 5-pin input for connection to VBV-711C shutter camera

3280**3982**

- 12-24Vdc
- 3 camera inputs
- Size (WxHxD)
5.8 x 4.3 x 1.2 inches
- 2 year warranty

**Features**

- 3 Auto-triggers
- Mirror / Normal switching from menu
- On-screen distance markers
- 'Button lock' anti-tamper feature
- Audio
- Sun shield
- Auto-dimmer
- Multi-lingual menus
- Auto-switching PAL / NTSC

Picture Quality

- LED backlighting
(gives 20,000 hours life)
- Anti-glare screen
- Resolution: 640 x 3 x 480

- Contrast ratio: 500:1
- Brightness: 200cd/m²
- Viewing angles:
Side 70° x Top 50° x Bottom 70°

Power

- Power consumption: 5 Watts
- Current: 0.18 Amps

Durability & Standards

- Mechanical vibration: 10G
- Mechanical shock: 100G
- Operating temperature: -4 to +158°F
- CE marked
- EMC approved: e
- HALT tested

Brigade Electronics Inc
226 S.Meridian St, Portland, IN 47371 USA
Tel: +1 (260) 766-4343 email: infousa@brigade-electronics.com
www.brigade-inc.com

