

MONITOR - BV-750 M

Features:

- Two camera inputs
- Automatic "screen on" when reversed gear engaged
- Camera one/camera two selector button
- Selector for changing the image Horizontal and Vertical
- 10G Mechanical Vibration
- Remote Controller
- Time ON/OFF selection
- Menu button to control Brightness, Contrast, Colour, Sharpness and Languages



Specification:

Picture Tube:	5.0" inch, colour TFT-LCD
Deflection angle	45°(left/right), 10°(top), 30°(down)
Power source:	12-24 vdc (with use of Control-Box) 12 vdc (without use of Control-Box)
Power consumption:	~ 8W/700mA maximum
Output voltage:	9.6vdc
TV System:	PAL/NTSC
Video Input/Output:	Composite Video Single 1Vp-p 75 ohm
Resolution:	960(H) x 234(V)
Viewing Angle (U x D x R/L):	15 x 35 x 50
Operating temperature:	0°C ~ to +60°C
Storage temperature range:	-25°C ~ +70°C
Weight:	0.43 kg
Dimensions: (W x H x T) mm:	168 x 125 x 30.5

CONTROL MODULE - BV-750 CM

Features:

- Two camera inputs
- 1 x AUDIO & 1 x VIDEO output
- 10G Mechanical Vibration



Specification:

Power source:	12-24 vdc
Video output:	1V p-p 75 ohm
Voltage output:	12 vdc
Operating temperature:	-15° to +60°C
Weight:	0.33 kg
Dimensions: (W x H x D)mm:	118 x 36 x 79

REVISIONS				PROPRIETARY NOTICE		BRIGADE ELECTRONICS PLC			
REV	DESCRIPTION	DATE	APPROVED	THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.		BV-750 MONITOR & CONTROL-BOX			
A	RELEASED	21/06/04	B.KHEZR			SIZE	STOCK CODE:	DWG NO	REV
							B1378/B1497	BE-SP-00013-00-04	A
								SHEET	1 OF 1