


Product Specification



UK

Model Number: DC-101-000 (6290)
(Part Number)

Optional accessories
DC-1XX-LOCK (6296)
DC-1XX-DPC7 (6323)

Dimensions: 78 x 34.6 x 31.5 mm

Key features	<p>Advanced Video Clear Technology</p> <p>Super Capacitor</p> <p>Integrated Thermal Protection</p> <p>Anti-File Corruption</p> <p>Parking Mode (Motion & Impact Detection)*</p> <p>Safety Camera Alert (Speed Camera, Red Light Camera) *</p> <p>GPS Port for GPS Antenna</p> <p>PC Viewer (Windows & Mac OS)</p> <p>Supports MicroSD Cards up to 64GB</p> <p>*Installation Required</p>	Package contents	<p>1 x DC-101</p> <p>1 x 16GB MicroSD card and SD Adaptor</p> <p>1 x GPS Sensor</p> <p>1 x 3m Hardwire cable</p> <p>1 x Windscreen Mount</p> <p>1 x 3M Sticky pad</p> <p>3 x 3M cable clips</p> <p>1 x Quick Start Guide</p>
---------------------	--	-------------------------	--

Dimensions / Weight	78 x 34.6 x 31.5 mm / 42.4g 3.1 x 1.4 x 1.2" / 0.1lb	
Memory	microSD memory card	- UHS-1: 16GB, 32GB, 64GB - Class 10: 8GB
Recording mode	<p>Continuous Rec</p> <p>Incident Rec</p> <p>Manual Rec</p> <p>Parking Rec (parking mode)</p>	<p>Records videos in 1-minute segments</p> <p>Records 10 seconds before and after the incident (total 20 seconds)</p> <p>Records from 10 seconds before and 50 seconds after manually starting the recording (total 1 minute)</p> <p>Requires the hardwiring cable installation</p>
Camera sensor	2.1M Pixel 1/2.7" CMOS 1080P	
Angle of view	Approximately 140°(diagonally)	
Video	FHD (1920 x 1080) / H.264 / file extension: MP4	
Frame rate	Maximum 30 fps	
Audio	PCM (pulse code modulation)	
Acceleration Sensor	Triaxial acceleration sensor (3D, +/-3G)	5 levels of sensitivity adjustment available
GPS	External GPS receiver	Safety driving section alert supported, stereo socket 2.5Ø / quadropole
Power input	DC 12 /24V supported	
Power consumption	2W (mean) / 14V	Except for the fully charged supercapacitor / GPS
Auxilliary power unit	Super capacitor	
LED Indicator	Status LED	
Key	REC key	Multi-function REC Key - Manual recording (press for 1 second) - Audio recording (press for 3 seconds) - Memory card format (press for 5 seconds)
Alarm	Built-in speakers	Voice guide (buzzer sounds)
Operating temperature	14 to 140°F / -10 to 60°C	
Storage temperature	-4 to 158°F / -20 to 70°C	