


Product Specification



Dimensions: 78 x 34.6 x 31.5 mm

UK/USA/EU/CAN

Model Number: (Part Number)
 DC-102-000 (6291) UK
 DC-102-001 (6561) USA
 DC-102-003 (6559) EU
 DC-102-003 (7032) CAN

Optional accessories
 DC-1XX-LOCK (6296)

Key features	Advanced Video Clear Technology Super Capacitor Integrated Thermal Protection Anti-File Corruption Parking Mode (Motion & Impact Detection)* Safety Camera Alert (Speed Camera, Red Light Camera)* GPS Port for GPS Antenna PC Viewer (Windows & Mac OS) Supports MicroSD Cards up to 64GB *Installation Required	Package contents	1 x DC-102 1 x 32GB MicroSD card and SD Adaptor (UK/USA/CAN) 1 x 64GB MicroSD card and SD Adaptor (EU) 1 x GPS Sensor 1 x 3m Hardwire cable 1 x Windscreen Mount 1 x 3M Sticky pad 3 x 3M cable clips 1 x Quick Start Guide
---------------------	--	-------------------------	---

Dimensions / Weight	78 x 34.6 x 31.5 mm / 42.4g 3.1 x 1.4 x 1.2" / 0.1lb	
Memory	microSD memory card	- UHS-1: 16GB, 32GB, 64GB - Class 10: 8GB
Recording mode	Continuous Rec Incident Rec Manual Rec Parking Rec (parking mode)	Records videos in 1-minute segments Records 10 seconds before and after the incident (total 20 seconds) Records from 10 seconds before and 50 seconds after manually starting the recording (total 1 minute) Requires the hardwiring cable installation
Camera sensor	2.12MP Sony Exmor CMOS 1080P	
Angle of view	Approximately 135°(diagonally)	
Video	FHD (1920 x 1080) / H.264 / file extension: MP4	
Frame rate	Maximum 30 fps	
Audio	PCM (pulse code modulation)	
Acceleration Sensor	Triaxial acceleration sensor (3D, +/-3G)	5 levels of sensitivity adjustment available
2nd camera	V-IN port	Stereo socket 2.5Ø / quadropole
GPS	External GPS receiver	Safety driving section alert supported, stereo socket 2.5Ø / quadropole
Power input	DC 12 /24V supported	
Power consumption	2ch: 3.25W / 1ch: 2.2W (mean)	Except for the fully charged supercapacitor / GPS
Auxilliary power unit	Super capacitor	
LED Indicator	Status LED	
Key	REC key	Multi-function REC Key - Manual recording (press for 1 second) - Audio recording (press for 3 seconds) - Memory card format (press for 5 seconds)
Alarm	Built-in speakers	Voice guide (buzzer sounds)
Operating temperature	14 to 140°F / -10 to 60°C	
Storage temperature	-4 to 158°F / -20 to 70°C	
Certifications	UKCA, CE, FCC & IC	

Technical: +44(0) 1322 420347
 www.brigade-electronics.com

Specifications subject to change without notice

PS(Various)-01 DC-102-00X