

Single Lens Dashcam



Product Specification



Model Number:

C6-Lite 2.0S (UK/EU) (8207)

Key features	Front road wide-angle lens, supports up to 1080P HD recording
	Supports expansion of one AHD camera for DMS algorithm
	Supports up to 2 channels of recording
	Supports H.264/H.265 encoding
	Supports 2*512GB dual Micro SD card storage, supports simultaneous saving of main stream and substream
	Built-in Wi-Fi, 4G communication module, and standard positioning module (optional installation of an inertial navigation module)
	Audio and video data supports AES256 encryption, data transmission supports TLS1.3 encryption protocol
	Supports 2 IO inputs, 1 IO output, and 1 selectable CAN or RS232 port
	Supports OBD power supply for convenient and quick installation
	Built-in ADAS function, supports lane departure, forward collision, and headway monitoring
	Supports sleep mode and remote wake-up
	Built-in 6-axis gravity sensor, supports detection of rapid acceleration, rapid deceleration, sharp turns, and collisions
Optional Driver Camera	720P Resolution
	Choice of A-Pillar, Dashboard or Windscreen mounting brackets
	4-pin aviation port and 2m tail cable
	Onboard AI processing to support detection of poor driving behaviours

Dimensions/Weight	116.5 x 66.98 x 79.2mm (including bracket)/271g	
Memory	MicroSD memory card	2 slots, 1 x 64GB Class 10 Industrial card included
Video	Forward facing 1080P/(h.264/h.265)	2nd input via expansion cable
GPS	Internal GPS receiver	
4G	LTE FDD: B1/B3/B7/B8/B20/B28A WCDMA: B1/B8 GSM: B3/B8	
Power Input	DC 12/24V supported	
Power consumption	7W Typical (11W Max) Standby approx. 4mA	
Operating temperature	-40°C - +70°C (-40°F - +158°F)	
Storage temperature	-40°C - +85°C (-40°F - +185°F)	
Certifications	CE/FCC/E-Mark Reg 10 Rev 06	