

MDSM-22 Fatigue Camera



Product Specification



Key features	<p>Compact and simple to install</p> <p>Minimal obstruction for driver's view</p> <p>Built-in GPS & Speaker</p> <p>Built-in WiFi for simple configuration using Mobile Apps (iOS and Android)</p> <p>Designed to protect the driver with timely alerts for:</p> <ul style="list-style-type: none"> - Drowsiness (eyes closing) - Yawning - Distraction and inattention - Smoking - Mobile use - No seat belt - Driver ID 	Package contents	<ul style="list-style-type: none"> 1 x MDSM-22 Camera 1 x MDSM-22 Main Control Box 1 x Main Cable 1 x Power Cable 1 x FMS Cable 1 x Ethernet Cable 1 x Bus & Truck bracket 1 x 3M Control Box Mounting Tape 1 x Camera Attachment Tape 1 x Camera fixing screw 2 x Control Box fixing screw 1 x Hexagonal wrench for MicroSD lock
---------------------	---	-------------------------	---

Dimensions / Weight	Camera body excl. cable and bracket	49.3 x 40.68 x 56.15mm / 244g inc. cable
	Control Box	80.8 x 148 x 27mm / 127g
OS	Embedded Linux	
CPU	ARM Cortex A7 Quad-Core@1.1GHz	
Memory	512MB NAND Flash, 1GB DDR3	
Power Input	12V to 32V DC	
GNSS	GPS / GLONASS / QZSS	
DSM Camera	88 degree, HD	
Interface	WiFi, Ethernet, RS-232, CAN	
SD Card	Up to 128GB, format free (optional)	
Temperature	Operating	-20°C to 70°C (-4°F to 158°F)
	Storage	-40°C to 85°C (-40°F to 185°F)