



- 1, RED 12-24VDC POSITIVE SUPPLY
- 2, ORANGE 12VDC POSITIVE OUTPUT
- 3, YELLOW 12-24VDC IGNITION SUPPLY
- 4, GREEN 12-24VDC POSITIVE REVERSE TRIGGER
- 5, BLUE 12-24VDC POSITIVE TRIGGER
- 6, BLACK 0VDC NEGATIVE

NOTE:
 ALL CAMERAS ARE RECORDED AT ALL TIMES INDEPENDENTLY OF WHAT IS SHOWN ON THE MONITOR.
 THE UNIT AND DIGITAL RECORDER DOES NOT REQUIRE A MONITOR TO BE CONNECTED FOR CORRECT OPERATION
 VCU-01 CONTINUES TO POWER DIGITAL RECORDER FOR 30mins AFTER IGNITION HAS BEEN TURNED OFF

M1 = VIDEO OUTPUT TO MONITOR
 C1 = INPUT FROM CAMERA 1 (REVERSE CAMERA)
 C2 = INPUT FROM CAMERA 2 (TOP DECK CAMERA)
 C3 = INPUT FROM CAMERA 3 (DDDR CAMERA)
 C4 = INPUT FROM CAMERA 4 (DRIVER CAMERA)
 C4 VIDEO SIGNAL DOES NOT CONNECT TO M1 MONITOR OUTPUT ONLY TO THE DIGITAL VIDEO RECORDER

PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC. AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by G.MABB		Checked by DKERAL	Approved by - date DKERAL - 07/03/08
		Filename GM	Date 07/03/2008
		Scale N/A	Scale N/A
		Edition 1/1	

BRIGADE ELECTRONICS
 VCU-01 (A1625)
 BE-000517-00-08