



- NOTES:**
- REFER TO BASE PRODUCT SPECIFICATIONS FOR MORE DETAILS.
  - THE OUTSIDE CABLE INSULATION MUST END MINIMUM 20MM WITHIN THE BOOT.
  - SINGLE WIRES TO CABLE CONNECTION MUST END MINIMUM 20MM WITHIN THE HEAT SHRINK.
  - FOR PACKAGING AND LABELING PLEASE REFER TO MASTER BILL OF MATERIALS.
  - LATEST FIRMWARE VERSION TO BE PRELOADED TO THE LED DISPLAY DURING MANUFACTURING (REFER TO BASE PRODUCT FOR FIRMWARE VERSION)
  - PD LABEL WILL BE ATTACHED TO A TAG AND PLACED ALONGSIDE PCB.

**PROPRIETARY NOTICE**  
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR EXPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS.



Assembly PI Approval M.LIN 06/08/2016	Approved by B.CHILDS	Checked by J.TYRRELL	Drawn by W.SINDEN
Angle of Projection 	Units mm	Scale N/A	Released 00/00/00
Status DRAFT	Assembly Ref BS-8000D-NH		
Part No 5448	BE-003816-00-18		