



NOTES:

1. EC-009 AUTO-OVERRIDE TIMER (DIAGRAM SHOWS STD 4S WIRING).
2. EC-009 WILL OPERAT ON 12 OR 24 VOLTAGE.
3. FOR 8 SECONDS TIMER CONNECT THE WIRE TO POSITIVE.
4. WHEN POWER IS APPLIED THE BACKALARM WILL SOUND FOR 4 OR 8 SECONDS, AFTER TIME OUT BACKALARM WILL NOT SOUND UNTIL UNIT IS RESET.

REVISIONS				PROPRIETARY NOTICE		EC-009	
REV	DESCRIPTION	DATE	APPROVED	THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.		SIZE	REV
A	RELEASED	06/03/03	D.KERAL			B0069	A
						DWG NO	
						BE-00053-00-03	
						SCALE	
				1 : 1	SHEET	1 OF 1	