



16 GA. WIRE - 12" LONG
 RED, POSITIVE (+)
 BLK, NEGATIVE (-)

.88 x .33 SLOTS (4) PL.
 [22 x 8]

NOTES:

1. TEMPERATURE RANGE:
 LOW: $-40^{\circ} \pm 5^{\circ} F$ ($-40^{\circ} \pm 3^{\circ} C$)
 HIGH: $185^{\circ} \pm 5^{\circ} F$ ($85^{\circ} \pm 3^{\circ} C$)
2. SURGE PROTECTION: ± 150 VDC FOR 400 MILLISECONDS
3. SPIKE PROTECTION: $+200$ OR $- 600$ VDC FOR 10 MILLISECONDS
4. FREQUENCY: 1250 Hz $\pm 20\%$
5. DUTY CYCLE: 1 PULSE PER SECOND - 50% ON 50% OFF
6. CASE: STEEL

NOTE: DIMENSIONS IN INCHES [MILLIMETERS]

PROPRIETARY NOTICE

THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

System Name		SA-901
Drawing No.	BE-00055-00-02	Prepared by
		D.Kerai
		31/10/02
BRIGADE BRIGADE ELECTRONICS PLC		