



- SPECIFICATION:
1. RATED VOLTAGE: 12-24VDC (WORKING VOLTAGE: 9 THUR 32 VDC)
 2. RATED CURRENT: 150mA
 3. SOUND PRESSURE: 102dBA AT TEST VOLTAGES OF 14-28 VOLTS
 4. FREQUENCY: 2600 +/- 200Hz
 5. INTERMITTENCE: 80+/- 10 CYCLES PER MINUTE AT TEST VOLTAGE
 6. VIBRATION RESISTANCE TO BE ABNORMALITY - FREE SUBJECT TO JIS D 1601 TD 7G
 7. WATER RESISTANCE TO BE ABNORMALITY FREE AS TESTED SUBJECT S1 D 0203 JIS D

ITEMREF	QUANTITY	TITLE/NAME, DESIGNATION, MATERIAL, DIMENTION ETC	ARTICLE NO./REFERENCE
DESIGNED BY M.BUTLER	CHECKED BY	APPROVED BY	DATE
BRIGADE ELECTRONICS PLC		FILE NAME MB	DATE 10/04/08
BA-059-102(S)		EDITION 0	SHEET 1/1
BE-000536-00-03			

PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.