



PRODUCTION LOT No.
 LAST DIGIT OF THE YEAR - PRODUCTION MONTH
 2002 - JAN=01
 FEB=02
 DEC=12

SPECIFICATION

- 1) RATED VOLTAGE: 12 - 24 VOLTS DIRECT CURRENT (WORKING VOLTAGE RANGE 9 THRU 32 VOLTS)
- 2) RATED CURRENT: 0.2 AMPERES OR LESS
- 3) SOUND PRESSURE: 97/44 DECIBELS AT TEST VOLTAGES OF 14-28 VOLTS, (AS MEASURED AT A DISTANCE OF 1.2 METERS AND AT A HEIGHT OF 1.2 METERS ABOVE THE GROUND)
- 4) FREQUENCY: 400±200Hz AT TEST VOLTAGES OF 14-28 VOLTS
- 5) INTERMITTENCE: 80±10 CYCLES PER MINUTE AT TEST VOLTAGES OF 14-28 VOLTS
- 6) DURABILITY : CONSECUTIVE 500 HOURS AT TEST VOLTAGES OF 28 VOLTS
- 7) SURGE VOLTAGE : TO BE FREE FROM ABNORMALITY WHEN APPLYING 100V,100ms PULSES FOR 5 SECONDS AT TEST VOLTAGE OF 28V
- 8) REVERSE POLARITY VOLTAGE PROTECTION: 400 VDC
- 9) RUSH CURRENT: 5 AMPERES, 5µs OR LESS AT A MAXIMUM VOLTAGE OF 32 VOLTS
- 10) RANGE OF OPERATING TEMP. GUARANTEED : -40C THRU 85C
- 11) WATER RESISTANCE : TO RESIST WATER AND BE ABNORMALLY-FREE AS TESTED SUBJECT TO ITEM S1, JIS D0203.
- 12) VIBRATION RESISTANCE : TO SATISFY A REQUIREMENT OF 10G SPECIFIED FOR SAE E994.
- 13) DUST PROOFNESS : TO BE ABNORMALLY-FREE AFTER SUBJECT TO ITEM F2, JIS D0207
- 14) OTHERS: SUBJECT TO SAE-J994B

Item ref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by B.KHEZR	Checked by D.KERAI	Approved by - date 25/05/03	File name BA-160 Date 25/06/04 Scale N/A

PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

BRIGADE ELECTRONICS		BA-160 (1279)
BE-00162-00-04	Edition 0	Sheet 1/1