



*本体にコード Assy をセットし出荷する。
ASSEMBLY BODY LEAD ASSY.

NOTES

1. HOUSING.
2. COVER.
3. TERMINAL.
4. PRONUNECIATION BODY.
5. BA-319-01 LEAD ASSEMBLY.

SPECIFICATION

- | | |
|--------------------------|--|
| 1. RATED VOLTAGE: | 12-24V DC (WORKING VOLTAGE RANGE 9 THRU 30 VOLTS). |
| 2. RATED CURRENT: | 50mA AND BELOW AT RATED VOLTAGE. |
| 3. SOUND PRESSURE: | 90+/- 10dB AT DISTANCE OF 1METRE RATED AT HEIGHT OF 1 METRE ABOVE THE GROUND AND AT RATED VOLTAGE. |
| 4. FREQUENCY: | 3000+/- 400 Hz AT RATED VOLTAGE. |
| 5. INTERMITTENCY: | 85+/- 10 CYCLES/MIN AT RATED VOLTAGE. |
| 6. STARTING VOLTAGE: | INTERMITTENT SOUND SHALL BE PRODUCED AT 9 V DC. |
| 7. VIBRATION RESISTANCE: | JIS D 1601 @ 4.5G AT FREQ. 33.33Hz |
| 8. WATER RESISTANCE: | JIS D 0203 |
| 9. DURABILITY: | CONT. OPERATION FOR 500HRS AT RATED VOLTAGE |

PROPRIETARY NOTICE

THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

System Name		BA-319 12/24V
Drawing No.	BE-00046-00-02	Prepared by D.Kerai
		2011.02
BRIGADE BRIGADE ELECTRONICS PLC		