



**SPECIFICATION**

- 1 RATED VOLTAGE: 12-24 VOLTS DIRECT CURRENT (WORKING VOLTAGE RANGE 9 THRU 32 VOLTS)
- 2 RATED CURRENT: 0.2 AMPERES OR LESS
- 3 SOUND PRESSURE: 97±4 DECIBELS AT TEST VOLTAGES OF 14-28 VOLTS, (AS MEASURED AT A DISTANCE OF 1.2 METERS AND AT A HEIGHT OF 1.2 METERS ABOVE THE GROUND)
- 4 FREQUENCY: 1400±200Hz AT TEST VOLTAGES OF 14-28 VOLTS
- 5 INTERMITTENCE: 80±10 CYCLES PER MINUTE AT TEST VOLTAGES OF 14-28 VOLTS
- 6 DURABILITY: CONTINUOUS 500 HOURS AT TEST VOLTAGE OF 32 VOLTS
- 7 RANGE OF OPERATING TEMP. GUARANTEED: -40C THRU 85C
- 8 SURGE VOLTAGE TEST: TO BE ABNORMALITY-FREE AS TESTED SUBJECT TO ISO7637 ITEM 3a, 3b, 5.
- 9 CONFORMS TO: SAEJ1994

PROPRIETARY NOTICE  
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC. AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by DKERAL		Checked by DKERAL	Date 22/04/2006
		Approved by - date DKERAL - 21/01/04	Filename XXX
BRIGADE ELECTRONICS		BA-460 (IDC)	
		BE-000382-00-06	
		Edition A	
		Scale 1/1	
		Sheet 1/1	