



SPECIFICATION

- 1, RATED VOLTAGE:12-24VDC(WORKING VOLTAGE RANGE 9 THRU 32VDLTS)
- 2, RATED CURRENT:0.3AMPARES DR LESS
- 3, SOUND PRESSURE:102+/-4 DECIBELS AT TEST VOLTAGES OF 14-28VDLTS (AS MEASURED AT A DISTANCE OF 1.2 METRES AND AT A HEIGHT OF 1.2 METRES ABOVE THE GROUND)
- 4, FREQUENCY: 1400+/-200HZ AT TEST VOLTAGES OF 14-28VDLTS
- 5, INTERMITTENCE:80+/-10 CYCLES PER MINUTE AT TEST VOLTAGES OF 14-28VDLTS
- 6, DURABILITY: CONTINUOUS 500 CYCLES AT TEST VOLTAGE OF 32VDLTS
- 7, RANGE OF OPERATING TEMP. GUARANTEED:-40C THRU 85C
- 8, SURGE VOLTAGE TEST: TD BE ABNDRMALITY-FREE AS TESTED SUBJECT TD ISO7637 ITEM 3a,3b,5
- 9, CONFRMS TD: SAEJ994

PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS PLC. AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS PLC.

Itemref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by DKERAL	Checked by DKERAL	Approved by - date DKERAL - 21/01/04	Filename XXX
BRIGADE ELECTRONICS		BA-470	Scale 1/1
BE-000378-00-06		Edition A	Sheet 1/1