



**SPECIFICATION:**

1. RATED VOLTAGE: 12/24 VOLTS DIRECT CURRENT (WORKING VOLTAGE RANGE 9 ~ 32 VOLTS)
2. RATED CURRENT: 0.3 AMPERES OR LESS
3. SOUND PRESSURE: 97±4 DECIBELS AT TEST VOLTAGE OF 14/28 VOLTS ( AS MEASURED AT A DISTANCE OF 1.2 METERS AND AT A HEIGHT OF 1.2 METERS ABOVE THE GROUND)
4. FREQUENCY: 1600±200Hz AT TEST VOLTAGE OF 14/28 VOLTS.
5. INTERMITTENCE: 80±15 CYCLES PER MINUTE AT TEST VOLTAGES OF 14/28 VOLTS.
6. DURABILITY: TO BE FREE OF ABNORMALITY AFTER BEING TESTED FOR 500 HOURS CONTINUOUSLY AT TEST VOLTAGES OF 32 VOLTS.
7. RANGE OF OPERATING TEMPERATURE GUARANTEED: -40°C ~ +85°C
8. OTHERS: SUBJECT TO SAE J994

- NOTES:**
1. FINISH IS BLACK.
  2. "R TRIANGLE" INDICATES CHANGES MADE TO REVISION AS IDENTIFIED IN NOTES.
  3. FOR PACKAGING & LABELLING DETAIL REFER TO THE LATEST REVISION OF THE MASTER BOM AND DRAWINGS.

**PROPRIETARY NOTICE**

THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS, AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR EXPROPRIATED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS.



Assembly Pl Approval w. FUKUZAWA		Approved by A. KEBEDE		Checked by S. ZHANG		Drawn by J. YU	
Angle of Projection		Units mm	Scale N/A	Released 17/03/2025	Assembly Ref -		
Third Angle		Status RELEASED		BA-560TC			
		Part No 274.7A		BE-005031-00-25			