



LAST DIGIT OF THE YEAR — PRODUCTION MONTH
 2001 — JAN=01
 FEB=02
 DEC=12

SPECIFICATION

- 1) RATED VOLTAGE: 24 VOLTS DIRECT CURRENT(WORKING VOLTAGE RANGE 18THRU 32 VOLTS)
- 2) RATED CURRENT: 20 MILLIAMPERES OR LESS
- 3) SOUND PRESSURE: 90±5 DECIBELS AT TEST VOLTAGES OF 28 VOLTS,
(AS MEASURED AT A DISTANCE OF 1 METERS AND AT A HEIGHT OF 1 METERS ABOVE THE GROUND)
- 4) FREQUENCY: 3100±400Hz AT TEST VOLTAGES OF 28 VOLTS
- 5) INTERMITTENCE: 80±10 CYCLES PER MINUTE AT TEST VOLTAGES OF 28 VOLTS

NOTES:

- 1) FRONT CASE
- 2) BACK CASE
- 3) NUT
- 4) SEAL RING
- 5) POWER CORD ASSY

Item#ref	Quantity	Title/Name, designation, material, dimension etc	Article No./Reference
Designed by B.KHEZR	Checked by D.KERAI	Approved by - date 22/06/04	File name CT-320
			Date 22/06/04
			Edition 0
			Scale NA

PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS P.L.C. AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR APPROPRIATE BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS P.L.C.

BRIGADE ELECTRONICS

VCT-320 (A1361)

BE-000301-00-04

Edition 0 Sheet 1/1