



- SPECIFICATIONS:**
1. RATED VOLTAGE: 12/24VDC.
 2. WORKING VOLTAGE: 9V-32VDC
 3. RATED CURRENT: 50mA.
 4. SOUND PRESSURE: 90±10dB(A) TESTED AT RATED VOLTAGE. (AS MEASURED AT A DISTANCE OF 1M AND AT A HEIGHT OF 1M ABOVE THE GROUND)
 5. FREQUENCY: 2900±500HZ AS POWERED AT RATED VOLTAGE.
 6. INTERMITTENCE: 95±10 CYCLES PER MINUTE AT RATED VOLTAGE.
 7. VIBRATION RESISTANCE: REQUIREMENTS SPECIFIED IN 3.4 AND 5 ABOVE SHALL BE SATISFIED AFTER SUBJECTING AS VIBRATED TO 6.8G 33.3Hz 2000C/min UP AND DOWN FOR 4H-RIGHT AND LEFT FOR 2HR UNDER CLASS 7 JIS D1610.
 8. DURABILITY: REQUIREMENTS SPECIFIED IN 3.4.5 SHALL BE SATISFIED AFTER SUBJECTING TO TEST OF CONSECUTIVE 500H- AT TEST VOLTAGE OF 28V±0.5V.
 9. THERMAL RESISTANCE: REQUIREMENTS SPECIFIED IN 3.4 AND 5 SHALL BE SATISFIED UPON RECOVERY OF ROOM TEMPERATURE AFTER EXPOSED TO 60°C AND -20°C FOR 1Hr 10.
 10. WATER RESISTANCE: TO BE FREE FROM ABNORMALITY AFTER TESTED AS SPECIFIED ON NO.3.4.5 IN S1 JIS D0203.
 11. SURGE VOLTAGE RESISTANCE: TO BE FREE FROM ABNORMALITY FOR UP TO 10ms AT 80 VOLTS.

- NOTES:**
1. FOR PRODUCT LABEL, REFER TO LATEST REVISION OF DRAWING BE-002833-XX-14.
 2. FOR GIFTBOX LABEL, REFER TO LATEST REVISION OF DRAWING BE-002834-XX-14.
 3. "R" TRIANGLE INDICATES CHANGES MADE TO REVISION AS IDENTIFIED IN NOTES.



PROPRIETARY NOTICE
 THIS DESIGN AND TECHNICAL INFORMATION APPEARING ON THIS DRAWING IS THE PROPERTY OF BRIGADE ELECTRONICS AND IS DISCLOSED IN CONFIDENCE. IT IS NOT TO BE COPIED, REPRODUCED, REVEALED TO OR EXPLOITED BY OTHERS, EITHER IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN CONSENT OF BRIGADE ELECTRONICS.

Revision Notes			
R1 - NOTES UPDATED TO INCLUDE LABEL DETAILS AS PER ECR CR -A274.			
APPA KUIDA	Drawn/RATES	Checked/MIBUTER	Approved/GPUTH
			Date: 28/08/14

Assembly PI Approval		Approved by		Checked by		Drawn by	
-		DKERAL		DKERAL		DKERAL	
Angle of Projection		Units		Scale		Released	
Third Angle		mm		N/A		22/11/05	
		Status		RELEASED		VRA-390	
		Part No		1545		BE-000349-01-05	

BRIGADE
 www.brigade-electronics.com

