

SIDESCAN® ULTRASONIC DETECTION SYSTEM

SS-4000W - Sidescan sensor system

3711



- 4 sensor system
- 12-24 Volts
- 1.0/1.5m detection range - (selectable via dip switch)
- Audible distance warning
- Underslung and flush-mount fixings included
- 2 levels of sensitivity - (selectable via dip switch)
- 2 year warranty

Contents

- 4 x sensors
- Buzzer
- 4 x 0° flush mount fixings
- 4 x 11° flush mount fixings
- 4 x underslung fixings
- Waterproof control box
- 10m buzzer cable
- 4 x 4.5m sensor cables
- 2 x 2.5m extension cables

Features

- Obstacles detected in under 200 milliseconds
- Environment Learning Mode prevents false alarms from ancillary

equipment that intrudes in the first 100cm of the detection zone

- Self-diagnostic function

Durability & Standards

- Operating temperature - -40 to +80°C
- Waterproof sensors to IP68
- Waterproof control box to IP69K
- CE marked
- EMC approved: E

ADDITIONS FOR ARTICULATED VEHICLES

SK-15-04	Truck/trailer camera/sensor cable kit - see p16	3997
SK-UDS-05	Truck/trailer sensor only cable kit (required)	4219
UDS-10BC	10m display cable (required)	3716
SS-4000W	Additional Sidescan sensor system for cab (optional)	3711

RECOMMENDED EXTRA



LS-20-A	Low speed trigger module (enables sensors below designated speed)	3177
---------	---	------



TS-001ECU	Turn indicator trigger for system activation	1362
-----------	--	------



OPTIONAL EXTRA

SS-BC-08	Backchat speaking alarm with side turn warning for cyclists/pedestrians	1334
----------	---	------

