

## SIDESCAN® ULTRASONIC DETECTION SYSTEM

### SS-4000W - Sidescan sensor system

3711



- 4 sensor system
- 12-24 Volts
- 3'/5' detection range - (selectable via dip switch)
- Audible distance warning
- Underslung and flush-mount fixings included
- 2 levels of sensitivity - (selectable via dip switch)
- 2 year warranty

#### Contents

- 4 x sensors
- Buzzer
- 4 x 0° flush mount fixings
- 4 x 11° flush mount fixings
- 4 x underslung fixings
- Waterproof control box
- 33' buzzer cable
- 4 x 15' sensor cables
- 2 x 8' extension cables

#### Features

- Obstacles detected in under 200 milliseconds
- Environment Learning Mode prevents false alarms from ancillary

equipment that intrudes in the first 3' of the detection zone

- Self-diagnostic function

#### Durability & Standards

- Operating temperature - -40 to +176°F
- Waterproof sensors to IP68
- Waterproof control box to IP69K
- CE marked
- EMC approved: E

### ADDITIONS FOR ARTICULATED VEHICLES

|           |                                                      |      |
|-----------|------------------------------------------------------|------|
| SK-15-04  | Truck/trailer camera/sensor cable kit - see p17      | 3997 |
| SK-UDS-05 | Truck/trailer sensor only cable kit (required)       | 4219 |
| UDS-10BC  | 33' display cable (required)                         | 3716 |
| SS-4000W  | Additional Sidescan sensor system for cab (optional) | 3711 |

### RECOMMENDED EXTRA



|           |                                                                   |      |
|-----------|-------------------------------------------------------------------|------|
| LS-20-A   | Low speed trigger module (enables sensors below designated speed) | 3177 |
| TS-001ECU | Turn indicator trigger for system activation                      | 1362 |

