

SELECT BACKSCAN REVERSING SENSOR SYSTEM



1. CHOOSE A BASE SYSTEM

BS-400A - 1.5m detection range system	2619A
BS-420A - 2.5m detection range system	2625A



Base system includes 7.5 metres of cabling

- 12-24 Volts
- Detection range shown above (outer sensors 0.6m)
- Underslung or flush-mount 4 sensor system
- 2 year warranty

Features

- Dynamic Scanning
- Memory prevents false alarms from tow-hooks and other ancillary equipment that intrude in the first 40cm of the detection zone
- Self-diagnostic function
- Buzzer with graduated audible distance warning
- Interchangeable sensors

Durability & Standards

- Operating temperature - buzzer & display: -20 to +60°C
- Operating temperature - ECU & sensors: -30 to +80°C
- Waterproof sensors to IP67
- CE marked
- EMC approved: E

2. CHOOSE A SENSOR TYPE



BS-KMPA-4	Flush mount sensor x 4 (not suitable for metal bumpers)	3241
------------------	--	-------------



BS-KBPA-4	Flush mount 11° upward angle sensor x 4 (suitable for all bumpers)	3239
------------------	---	-------------



BS-KXPA-4	Underslung sensor x 4	3240
------------------	------------------------------	-------------

3. OPTIONAL EXTRAS



BS-VDM-01	Visual display with 5 metres of cable	1511
------------------	--	-------------



BS-10XA	10 metre buzzer and display extension cables	2623
----------------	---	-------------



BS-10CBZ	10 metre buzzer extension cable	3073
-----------------	--	-------------



BS-22HC	Sensor hole cutter (22mm for metal or plastic)	1237
----------------	---	-------------

