

## ESSENTIAL BACKSCAN REVERSING SENSOR SYSTEM



### 1. BASE SYSTEM

1.5m detection range system (add sensors to determine model)



Base system includes 5 metres of cabling

- 12-24 Volts
- 1.5m detection range (all sensors)
- Flush-mount 4 sensor system
- 2 year warranty

#### Features

- Dynamic Scanning
- Memory prevents false alarms from tow-hooks and other ancillary equipment that intrude in the first 40cm of the detection zone
- Buzzer with graduated audible distance warning

#### Durability & Standards

- Operating temperature - buzzer & display: -20 to +60°C
- Operating temperature - ECU & sensor: -20 to +80°C
- Waterproof sensors to IP67
- CE marked
- EMC approved: E

### 2. CHOOSE A SENSOR TYPE



**BS-400F-KMMA** Flush mount 5° upward angle 4 sensor system (not suitable for metal bumpers) **2608**



**BS-400F-KB** Flush mount 7° upward angle 4 sensor system (suitable for all bumpers) **2609**

### 3. OPTIONAL EXTRAS



**BS-VDM-02** Visual display with 5 metres of cable **2624**



**BS-10XA** 10 metre buzzer and display extension cables **2623**



**BS-10CBZ** 10 metre buzzer extension cable **3073**



**BS-22HC** Sensor hole cutter (22mm for metal or plastic) **1237**

