

SIDESCAN® ULTRASONIC DETECTION SYSTEM

SS-4000W - Sidescan sensor system

3711



- **4 sensor system**
- **12-24 Volts**
- **3'/5' detection range - (selectable via dip switch)**
- **Audible distance warning**
- **Underslung and flush-mount fixings included**
- **2 levels of sensitivity - (selectable via dip switch)**
- **2 year warranty**

Contents

- 4 x sensors
- Buzzer
- 4 x 0° flush mount fixings
- 4 x 11° flush mount fixings
- 4 x underslung fixings
- Waterproof control box
- 33' buzzer cable
- 4 x 15' sensor cables
- 2 x 8' extension cables

Features

- Obstacles detected in under 200 milliseconds
- Environment Learning Mode prevents false alarms from ancillary

equipment that intrudes in the first 3' of the detection zone

- Self-diagnostic function

Durability & Standards

- Operating temperature -40 to +176°F
- Waterproof sensors to IP68
- Waterproof control box to IP69K
- CE marked
- EMC approved: E

ADDITIONS FOR ARTICULATED VEHICLES

SK-15-04	Truck/trailer camera/sensor cable kit - see p17	3997
SK-UDS-05	Truck/trailer sensor only cable kit (required)	4219
UDS-10BC	33' display cable (required)	3716
SS-4000W	Additional Sidescan sensor system for cab (optional)	3711

RECOMMENDED EXTRA



LS-20-A	Low speed trigger module (enables sensors below designated speed)	3177
TS-001ECU	Turn indicator trigger for system activation	1362

